

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/041164

International filing date: 01 December 2004 (01.12.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/527,895
Filing date: 05 December 2003 (05.12.2003)

Date of receipt at the International Bureau: 17 January 2005 (17.01.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

January 10, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/527,895

FILING DATE: *December 05, 2003*

RELATED PCT APPLICATION NUMBER: *PCT/US04/41164*



Certified By

Jon W Dudas

Under Secretary
of Commerce for Intellectual Property
and Acting Director of the
United States Patent and Trademark Office

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.


PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

| INVENTOR(S) | | | | | |
|---|------------------------|---|----------------|--|------------------------|
| Given Name (first and middle [if any]) | Family Name or Surname | Residence (City and either State or Foreign Country) | | | |
| Jeff | Cooper | Rocky Hill, New Jersey | | | |
| Jill | Boyce | Manalapan, New Jersey | | | |
| <input checked="" type="checkbox"/> Additional inventors are being named on the <u>1</u> separately numbered sheets attached hereto | | | | | |
| TITLE OF THE INVENTION (500 characters max) | | | | | |
| FILM GRAIN SIMULATION AND COMFORT NOISE ADDITION SPECIFICATION FOR DIRECTV A3 SYSTEM | | | | | |
| Direct all correspondence to: | | CORRESPONDENCE ADDRESS | | | |
| <input type="checkbox"/> Customer Number | | | | | |
| OR | | | | | |
| <input checked="" type="checkbox"/> Firm or Individual Name | | JOSEPH S. TRIPOLI, THOMSON LICENSING INC. | | | |
| Address | | PATENT OPERATIONS | | | |
| Address | | P. O. BOX 5312 | | | |
| City | PRINCETON | State | NJ | ZIP | 08543-5312 |
| Country | USA | Telephone | 609 - 734-6834 | Fax | 609 - 734-6888 |
| ENCLOSED APPLICATION PARTS (check all that apply) | | | | | |
| <input checked="" type="checkbox"/> Specification Number of Pages | | <u>18</u> | | <input type="checkbox"/> CD(s), Number <u> </u> | |
| <input type="checkbox"/> Drawing(s) Number of Sheets | | <u> </u> | | <input type="checkbox"/> Other (specify) <u> </u> | |
| <input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76 | | | | | |
| METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT | | | | | |
| <input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. | | | | | |
| <input type="checkbox"/> A check or money order is enclosed to cover the filing fees | | | | | |
| <input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: <u>07-0832</u> | | | | | FILING FEE AMOUNT (\$) |
| <input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached. | | | | | 160 |
| The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government. | | | | | |
| <input type="checkbox"/> No. | | | | | |
| <input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: <u> </u> | | | | | |

Respectfully submitted,

SIGNATURE



[Page 1 of 2]

Date

12/5/03

TYPED or PRINTED NAME

Robert B. Levy

REGISTRATION NO.

28,234

(if appropriate)

Docket Number:

PU030308

TELEPHONE

609-734-6820

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

17548 U.S. PTO
60/527895



120503

The PTO did not receive the following listed item(s) & pages of specification

PROVISIONAL APPLICATION COVER SHEET
Additional Page

PTO/SB/16 (08-03)

Approved for use through 07/31/2006. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

| Docket Number PU030308 | | |
|--|-------------------|---|
| INVENTOR(S)/APPLICANT(S) | | |
| Given Name (first and middle [if any]) | Family or Surname | Residence (City and either State or Foreign Country) |
| Alexandros | Tourapis | West Windsor, New Jersey |
| Cristina | Gomila | Princeton, New Jersey |
| Joan | Llach | Princeton, New Jersey |
| Peng | Yin | West Windsor, New Jersey |

[Page 2 of 2]

Number 2 of 2

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

FEE TRANSMITTAL for FY 2003

Effective 01/01/2003. Patent fees are subject to annual revision.

☐ Applicant claims small entity status. See 37 CFR 1.27

TOTAL AMOUNT OF PAYMENT (\$) 160

Complete if Known

Application Number _____
Filing Date _____
First Named Inventor Jeff Cooper
Examiner Name _____
Art Unit _____
Attorney Docket No. PU030308

METHOD OF PAYMENT (check all that apply)

☐ Check ☐ Credit card ☐ Money Order ☐ Other ☐ None

☒ Deposit Account:

Deposit Account Number 07-0832

Deposit Account Name THOMSON LICENSING INC.

The Director is authorized to: (check all that apply)

☒ Charge fee(s) indicated below ☒ Credit any overpayments
☐ Charge any additional fee(s) during the pendency of this application
☐ Charge fee(s) indicated below, except for the filing fee to the above-identified deposit account.

FEE CALCULATION

1. BASIC FILING FEE

| Large Entity | | Small Entity | | Fee Description | Fee Paid |
|---------------------|----------|--------------|----------|------------------------|-----------------|
| Fee Code | Fee (\$) | Fee Code | Fee (\$) | | |
| 1001 | 770 | 2001 | 385 | Utility filing fee | |
| 1002 | 340 | 2002 | 170 | Design filing fee | |
| 1003 | 530 | 2003 | 265 | Plant filing fee | |
| 1004 | 770 | 2004 | 385 | Reissue filing fee | |
| 1005 | 160 | 2005 | 80 | Provisional filing fee | 160 |
| SUBTOTAL (1) | | | | | (\$ 160) |

2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE

Total Claims - ** = X =
Independent Claims - ** = X =
Multiple Dependent X =

| Large Entity | | Small Entity | | Fee Description | Fee Paid |
|---------------------|----------|--------------|----------|--|---------------|
| Fee Code | Fee (\$) | Fee Code | Fee (\$) | | |
| 1202 | 18 | 2202 | 9 | Claims in excess of 20 | |
| 1201 | 86 | 2201 | 43 | Independent claims in excess of 3 | |
| 1203 | 290 | 2203 | 145 | Multiple dependent claim, if not paid | |
| 1204 | 86 | 2204 | 43 | ** Reissue independent claims over original patent | |
| 1205 | 18 | 2205 | 9 | ** Reissue claims in excess of 20 and over original patent | |
| SUBTOTAL (2) | | | | | (\$ 0) |

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)

3. ADDITIONAL FEES

| Large Entity | | Small Entity | | Fee Description | Fee Paid |
|--------------|----------|--------------|----------|--|----------|
| Fee Code | Fee (\$) | Fee Code | Fee (\$) | | |
| 1051 | 130 | 2051 | 65 | Surcharge - late filing fee or oath | |
| 1052 | 50 | 2052 | 25 | Surcharge - late provisional filing fee or cover sheet. | |
| 1053 | 130 | 1053 | 130 | Non-English specification | |
| 1812 | 2,520 | 1812 | 2,520 | For filing a request for reexamination | |
| 1804 | 920* | 1804 | 920* | Requesting publication of SIR prior to Examiner action | |
| 1805 | 1,840* | 1805 | 1,840* | Requesting publication of SIR after Examiner action | |
| 1251 | 110 | 2251 | 55 | Extension for reply within first month | |
| 1252 | 420 | 2252 | 210 | Extension for reply within second month | |
| 1253 | 950 | 2253 | 475 | Extension for reply within third month | |
| 1254 | 1,480 | 2254 | 740 | Extension for reply within fourth month | |
| 1255 | 2,010 | 2255 | 1,005 | Extension for reply within fifth month | |
| 1401 | 330 | 2401 | 165 | Notice of Appeal | |
| 1402 | 330 | 2402 | 165 | Filing a brief in support of an appeal | |
| 1403 | 290 | 2403 | 145 | Request for oral hearing | |
| 1451 | 1,510 | 1451 | 1,510 | Petition to institute a public use proceeding | |
| 1452 | 110 | 2452 | 55 | Petition to revive - unavoidable | |
| 1453 | 1,330 | 2453 | 665 | Petition to revive - unintentional | |
| 1501 | 1,330 | 2501 | 665 | Utility issue fee (or reissue) | |
| 1502 | 480 | 2502 | 240 | Design issue fee | |
| 1503 | 640 | 2503 | 320 | Plant issue fee | |
| 1460 | 130 | 1460 | 130 | Petitions to the Commissioner | |
| 1807 | 50 | 1807 | 50 | Processing fee under 37 CFR 1.17 (q) | |
| 1806 | 180 | 1806 | 180 | Submission of Information Disclosure Stmt | |
| 8021 | 40 | 8021 | 40 | Recording each patent assignment per property (times number of properties) | |
| 1809 | 770 | 2809 | 385 | Filing a submission after final rejection (37 CFR § 1.129(a)) | |
| 1810 | 770 | 2810 | 385 | For each additional invention to be examined (37 CFR § 1.129(b)) | |
| 1801 | 770 | 2801 | 385 | Request for Continued Examination (RCE) | |
| 1802 | 900 | 1802 | 900 | Request for expedited examination of a design application | |

Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3)

(\$ 0)

SUBMITTED BY

| | | | | | |
|-------------------|----------------|-----------------------------------|--------|-----------|------------------|
| Name (Print/Type) | Robert B. Levy | Registration No. (Attorney/Agent) | 28,234 | Telephone | 609-734-6820 |
| Signature | | | | Date | December 5, 2003 |

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

This collection of information is required by 37 CFR 1.17 and 1.27. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing this form, call 1-800-PTO-9199 (1-800-786-9199) and select option 2.

Express Mail Label no. EV 413 351 704 05

PV030308

Film Grain Simulation and Comfort Noise Addition Specification for DirecTV A3 System

1 INTRODUCTION

This document provides a specification for film grain simulation and comfort noise addition in a DirecTV A3 system.

The film grain simulation is based on the contribution JVT-I013r2 [1] adopted at the 7th JVT meeting. Constraints of the DirecTV system regarding the value of the parameters of the SEI message and some implementation aspects are described.

Comfort noise addition reuses hardware elements of the film grain simulation to hide compression artifacts.

2 FILM GRAIN SIMULATION

2.1 FILM GRAIN SEI Message Constraints

The film grain generator makes use of the parameters specified in the SEI message described in [1, 2]. Limitations regarding the SEI message are described.

Film grain SEI messages may only be sent preceding I pictures, and only one film grain SEI message may precede a particular I picture. I pictures are indicated by slice_type equal to 7, or by nal_ref_idc equal to 5.

model_id shall be 0. This identifies the film grain simulation model as frequency filtering.

colour_space_id shall be 0. This identifies the color space in which the parameters of the SEI message have been estimated as YCbCr.

PV030308

blending_mode_id shall be 0. This identifies the blending mode used to blend the simulated film grain with the decoded images as additive.

log2_scale_factor shall be in the range [2, 7].

comp1_param_present_flag shall be 0. This prevents the transmission of film grain parameters for the Cb color component.

comp2_param_present_flag shall be 0. This prevents the transmission of film grain parameters for the Cr color component.

no_intensity_intervals_minus1[0] shall be in the range [0, 7]. This gives the number of intensity intervals for which a specific set of parameters has been estimated.

intensity_interval_lower_bound[0][i+1] > **intensity_interval_upper_bound[0][i]** for $i=0 \dots 6$. This indicates that multi-generational film grain is not supported.

no_param_minus1[0] shall be in the range [0,2]. Low-pass modeling and cross-color correlation are not used.

param[0][i][0] shall be in the range [0, 255].

param[0][i][1] shall be in the range [3, 15].

param[0][i][2] shall be in the range [3, 15] and shall be transmitted only when not equal to **param[0][i][1]**. When both parameters are transmitted, ~~the allowed only the~~ pair of values are listed in Table 1 are allowed.

| param[0][i][1] | param[0][i][2] |
|----------------|----------------|
| 4 | 3 |
| 6 | 4 |
| 7 | 5 |
| 8 | 6 |
| 10 | 7 |
| 11 | 8 |
| 13 | 9 |
| 14 | 10 |
| 15 | 11 |

| | |
|----|----|
| 15 | 12 |
| 15 | 13 |
| 15 | 14 |
| 15 | 15 |

Table 1.

All the other parameters of the SEI message have no constraint with respect to the standard specification.

2.2 Film grain Implementation aspects

Film grain addition involves two distinct steps of operation. First, an initialization process is performed when an SEI message is received preceding an I picture, in which a pool of film grain blocks is created. Then, prior to display, a simple process is applied to add the stored film grain blocks to each luma pixel of each decoded picture.

2.2.1 Initialization at SEI message receipt to create film grain block pool

Upon receipt of a film grain SEI message, an initialization process is performed to create a pool of 4,096 (512x8) film grain pixel values for each of up to 8 different luma intensity intervals. The number of luma intensity intervals is indicated by 1 plus the SEI message field **no_intensity_intervals_minus1[0]**. Generation of the film grain samples begins with the lowest luma intensity interval.

Bit-accurate simulation of the film grain noise can be accomplished using a specified uniform pseudo-random number generator polynomial and using a specified database of film grain patterns. The database of film grain patterns is composed of 13 sets of 4,096 (512x8) values each. The values are stored in 2's complement form and range from [-127, 127]. The list of values for each set is shown in the Appendix.

The process to obtain the film grain pixel values for a particular luma intensity interval *s* is shown in the block diagram of Figure 1. The process specifies the access to the database of film grain patterns, the scaling of the values, and their storage into the pool as follows:

```
for( i = 0..4,095)
    v = param[0][s][0] * database[ m ][ n ][ i ]
    pool[ s ][ i ] = (((v + 2log2_scale_factor - 1) >> log2_scale_factor ) + 32) >> 6
```


PV030308

where n is equal to $\text{param}[0][s][2] - 3$, m is equal to 0 when **no_param_minus1[0]** is 1 and equal to 1 otherwise, and the factor 6 scales the film grain values provided in the Appendix.

This process is performed as many times as indicated by 1 plus the SEI message field **no_intensity_intervals_minus1[0]**.

2.2.2 Block and pixel operations prior to pixel display

The operations performed to add film grain to the decoded picture at block and pixel level are shown in Figure 2. For each 8x8 block of the decoded image, the average of the luma pixel values is computed and compared to the SEI message **intensity_interval_low-r_bound[0][i]** and **intensity_interval_upper_bound[0][i]** parameters to determine the correct luma intensity interval for the block.

A uniform random number generator, using a primitive polynomial modulo 2 operator, $x^{18} + x^5 + x^2 + x^1 + 1$, is used to select film grain blocks from the pool. Let $x(i, e)$ indicate the i -th symbol of the sequence x , beginning with an initial seed e . (The seed is set to 1 upon the receipt of each film grain SEI message.) The offset for the current 8x8 block of film grain is generated as follows:

```
previous_offset = offset
offset = (x(i, 1) % 4,088) >> 2
offset ^= (index == previous_offset)
offset <<= 2
```

where offset has been initialized to 0 after the creation of the pool. After the calculation of the offset, the 8x8 block of film grain is extracted from the pool as follows:


```
for (i=0..7, j=0..7)
    block[i][j] = pool[s][offset + i + j*4096]
```

Before blending the film grain block with the decoded image, deblocking of the pixels on the left and right columns of the block is performed as described in Section 2.2.2.1. The deblocked film grain block is then added to the decoded pixels and the result clipped to [0, 255] for display. Film grain noise is only added to luma pixels.

PV030308

2.2.2.1 Deblocking filter

As suggested in [1], a deblocking filter shall be applied on the film grain image before blending to smooth the blocking artifacts resulting from the small size of the transform. The deblocking filter is implemented by means of a 3-tap filter applied to all pixels bordering the 8x8 block left and right edges. Given a row of pixels belonging to two adjacent 8x8 blocks, the transition between blocks being located between pixels b and c,



the filter is applied as follows:

$$b' = (a + (b \ll 1) + c) \gg 2$$

$$c' = (b + (c \ll 1) + d) \gg 2$$

where b' and c' replace the value of the original pixels b and c, respectively. Deblocking of the left and right block edges is done for every block at display time.

3 COMFORT NOISE SPECIFICATION

Comfort noise addition is used to hide compression artifacts. Comfort noise addition and film grain simulation are not used at the same time. Unlike film grain simulation, it is not intended to match a pre-specified noise pattern (i.e. film grain).

A custom SEI message is proposed to enable turning comfort noise on and off, as well as indicating the level of noise to add, based on the expected level of compression artifacts.

Comfort noise addition utilizes several of the film grain simulation hardware elements.

3.1 Comfort noise SEI message

We propose use of a registered user data SEI message to indicate the use of comfort noise. It applies to all pictures that follow, until an IDR or a new comfort noise or film grain SEI message arrives. Comfort noise SEI messages may only be sent preceding I pictures, and only one

P0030308

comfort noise SEI message may precede a particular I picture. I pictures are indicated by slice_type equal to 7, or by nal_ref_idc equal to 5.

| | | |
|---|---|------------|
| user_data_registered_itu_t_t35(payloadSize) { | C | Descriptor |
| itu_t_t35_country_code | 5 | b(8) |
| itu_t_t35_payload_byte | 5 | b(8) |
| comfort_noise_flag | 5 | u(1) |
| if (comfort_noise_flag == 1) { | | |
| comfort_noise_qp_offset_idc | 5 | ue(v) |
| comfort_noise_qp_weight_offset_idc | 5 | ue(v) |
| } | | |
| } | | |

comfort_noise_flag equal to 1 indicates that comfort noise addition is used.

comfort_noise_flag equal to 0 indicates that comfort noise addition is not used.

comfort_noise_qp_offset_idc indicates the quantization parameter offset used in the calculation of the additive comfort noise level, and may range in value from -51 to 52.

comfort_noise_qp_weight_offset_idc indicates a quantization parameter weight offset used in the calculation of the additive comfort noise level, and may range in value from -6 to 7.

3.2 Comfort noise implementation aspects

Comfort noise addition includes operations performed at the block level, and operations performed at the pixel level. A key difference between film grain and comfort noise is the temporal correlation of additive comfort noise.

3.2.1 Block level operations

Per block operations are performed to calculate relative weights of the three terms used for comfort noise generation, as shown in Figure 3. The inputs to this process are decoded luma

P0030308

pixels, the picture QP = (pic_init_qp_minus26 + 26), and the **comfort_noise_qp_offset_idc** and **comfort_noise_qp_weight_offset_idc** from the comfort noise SEI message.

The current picture number is indicated by t. t is reset to 0 for the I picture that follows a comfort noise SEI message. The average of the 8x8 luma pixel block of the current picture, t, is calculated as block_avg(t) and compared to a threshold. If $\text{block_avg}(t) \geq 10$, block_avg_level = 1, otherwise block_avg_level = 0.

The absolute difference of the current luma block average with respect to the co-located block from the previous displayed picture is calculated, where t-1 indicates the previous displayed picture, and compared to a threshold. If $|\text{block_avg}(t) - \text{block_avg}(t-1)| > 3$, block_absdiff_level = 0, otherwise block_absdiff_level = 1. If t is equal to 0, block_absdiff_level = 1.

For SD resolutions and below, all pixel and block operations are done using the display resolution. For HD resolutions, block operations are performed using 2x2 sub-sampled pixels (using the upper left pixel of 2x2 pixels), so the 8x8 luma pixel avg involves adding $8 \times 8 = 64$ pixel values, but these values are spread over a 16x16 pixel range. For SD resolutions, storage of the block_avg values for the entire picture requires storage of 1/64 the size of a frame store. For HD resolutions, storage of block_avg values requires a storage of 1/256 the size of a frame store.

The values of **comfort_noise_qp_offset_idc**, **comfort_noise_qp_weight_offset_idc**, and picture QP, are used in the calculation of an *intermediate* weight w_q which is calculated as follows:

$$w_q = (\text{clip}((\text{weight}(\text{clip}(\text{QP} + \text{comfort_noise_qp_offset_idc}, 0, 51))) + \text{comfort_noise_qp_weight_offset_idc}), 0, 7)$$

where $\text{weight}(Q)$ is defined in Table 2Table 1.

| | | | | | | | | | | | | | |
|-----------|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Q | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| weight(Q) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Q | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 |
| weight(Q) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 2 | 2 | 2 |
| Q | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 |
| weight(Q) | 3 | 3 | 3 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 5 | 5 | 5 |
| Q | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 |
| weight(Q) | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 6 | 6 | 6 | 6 | 6 | 6 |

Table 21. weight(Q) lookup table

P0030308

The value of w_g , which needs to be computed only once for each picture, and the values of block avg level and block absdiff level are then input to a lookup table to find the values of the final weights, w_0 , w_1 , and w_f , which are used in the pixel level operations.

| w_g | block absdiff level | block avg level | w_f | w_1 | w_0 |
|-------|---------------------|-----------------|-------|-------|-------|
| 0 | 0 | 0 | 0 | 0 | 0 |
| | 0 | 1 | 0 | 0 | 0 |
| | 1 | 0 | 0 | 0 | 0 |
| | 1 | 1 | 0 | 0 | 0 |
| 1 | 0 | 0 | 12 | 11 | 25 |
| | 0 | 1 | 12 | 8 | 19 |
| | 1 | 0 | 30 | 10 | 14 |
| | 1 | 1 | 30 | 7 | 11 |
| 2 | 0 | 0 | 23 | 22 | 50 |
| | 0 | 1 | 23 | 17 | 38 |
| | 1 | 0 | 60 | 20 | 28 |
| | 1 | 1 | 60 | 14 | 21 |
| 3 | 0 | 0 | 35 | 34 | 76 |
| | 0 | 1 | 35 | 25 | 57 |
| | 1 | 0 | 90 | 29 | 42 |
| | 1 | 1 | 90 | 21 | 32 |
| 4 | 0 | 0 | 47 | 45 | 101 |
| | 0 | 1 | 47 | 34 | 76 |
| | 1 | 0 | 120 | 39 | 56 |
| | 1 | 1 | 120 | 28 | 42 |
| 5 | 0 | 0 | 59 | 56 | 126 |
| | 0 | 1 | 59 | 42 | 95 |
| | 1 | 0 | 150 | 49 | 70 |
| | 1 | 1 | 150 | 35 | 53 |
| 6 | 0 | 0 | 70 | 67 | 151 |
| | 0 | 1 | 70 | 50 | 113 |
| | 1 | 0 | 179 | 59 | 84 |
| | 1 | 1 | 179 | 42 | 63 |
| 7 | 0 | 0 | 82 | 78 | 176 |
| | 0 | 1 | 82 | 59 | 132 |
| | 1 | 0 | 209 | 69 | 98 |
| | 1 | 1 | 209 | 49 | 74 |

Table 32. Lookup table for comfort noise generation.

P0030308

Note that the determination of the current picture structure is based on display rather than coding structure. For interlaced display, pixels from the current field and previous field are used in the calculations. For progressive display, pixels from the current frame and previous frame are used in the calculations.

The values of block_avg_level and block_absdiff_level are input to a lookup table to find the values of sw_0 , sw_1 and sw_2 .

| block_avg_level | block_absdiff_level | block_avg_level | block_absdiff_level | block_avg_level | block_absdiff_level |
|-----------------|---------------------|-----------------|---------------------|-----------------|---------------------|
| 0 | 0 | 9 | 1 | 3 | 6 |
| 0 | 1 | 9 | 1 | 2 | 2 |
| 1 | 0 | 2 | 1 | 2 | 3 |
| 1 | 1 | 2 | 1 | 1 | 3 |

Table 2. Lookup table

P0030308

These values $\{sw_0, sw_1, sw_f\}$ and the values of the picture QP , **comfort_noise_qp_offset_idc**, and **comfort_noise_qp_weight_offset_idc** are then used in the calculation of the final weights, w_0 , w_1 and w_f , which are used in the pixel-level operations.

| | | | | | | | | | | | | | |
|-----------|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Q | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| weight(Q) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Q | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 |
| weight(Q) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 2 | 2 | 2 |
| Q | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 |
| weight(Q) | 3 | 3 | 3 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 5 | 5 | 5 |
| Q | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 |
| weight(Q) | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 6 | 6 | 6 | 6 | 6 | 6 |

Table 3. weight(Q) lookup table

With weight(Q) defined in Table 2,

$$w_q = -(\text{clip}((\text{weight}(\text{clip}(QP + \text{comfort_noise_qp_offset_idc}, 0, 51))) + \text{comfort_noise_qp_weight_offset_idc}), 0, 7)$$

$$w_0 = sw_0 * w_q$$

$$w_1 = sw_1 * w_q$$

$$w_f = sw_f * w_q$$

The above multiplies could be completely avoided if implemented with the use of a larger lookup table that also considers the value of w_q , and which can immediately compute w_0 , w_1 , and w_f without the intermediate calculations of sw_0 , sw_1 , and sw_f .

BEST AVAILABLE COPY

- 11 -

P0030308

| | | | | | |
|---|---|---|---|---|---|
| 3 | 0 | 0 | 2 | 4 | 1 |
| | | | 7 | 8 | 0 |
| | | | | | 8 |
| | 0 | 1 | 2 | 3 | 8 |
| 4 | | | 7 | 6 | 1 |
| | 1 | 0 | 6 | 4 | 6 |
| | | | 9 | 2 | 0 |
| | 1 | 1 | 6 | 3 | 4 |
| 5 | | | 9 | 0 | 5 |
| | 0 | 0 | 3 | 6 | 1 |
| | | | 6 | 4 | 4 |
| | | | | | 4 |
| 6 | 0 | 1 | 3 | 4 | 1 |
| | | | 6 | 8 | 0 |
| | | | | | 8 |
| | 1 | 0 | 9 | 5 | 8 |
| 7 | | | 2 | 6 | 0 |
| | 1 | 1 | 9 | 4 | 6 |
| | | | 2 | 0 | 0 |
| | | | | | |
| 8 | 0 | 0 | 4 | 8 | 1 |
| | | | 5 | 0 | 8 |
| | | | | | 0 |
| | 0 | 1 | 4 | 6 | 1 |
| 9 | | | 5 | 0 | 3 |
| | | | | | 5 |
| | 1 | 0 | 1 | 7 | 1 |
| | | | 1 | 0 | 0 |
| 0 | | | 5 | | 0 |
| | 1 | 1 | 1 | 5 | 7 |
| | | | 1 | 0 | 5 |
| | | | 5 | | |
| 1 | 0 | 0 | 5 | 9 | 2 |
| | | | 4 | 6 | 1 |
| | | | | | 6 |
| | 0 | 1 | 5 | 7 | 1 |
| 2 | | | 4 | 2 | 6 |
| | | | | | 2 |
| | 1 | 0 | 1 | 8 | 1 |
| | | | 3 | 4 | 2 |
| 3 | | | 8 | | 0 |
| | | | | | |
| | | | | | |
| | | | | | |

| | | | | | |
|---|---|---|---|---|---|
| | 1 | 1 | 1 | 6 | 9 |
| | | | 3 | 0 | 0 |
| | | | 8 | | |
| | 0 | 0 | 6 | 1 | 2 |
| | | | 3 | 1 | 5 |
| | | | 2 | 2 | |
| | 0 | 1 | 6 | 8 | 1 |
| | | | 3 | 4 | 8 |
| | | | | | 9 |
| 7 | 1 | 0 | 1 | 9 | 1 |
| | | | 6 | 8 | 4 |
| | | | 1 | | 0 |
| | 1 | 1 | 1 | 7 | 1 |
| | | | 6 | 0 | 0 |
| | | | 1 | | 5 |

Table 4. Expanded lookup table for multiplication avoidance.

Note that the determination of the current picture structure is based on display rather than coding structure. For interlaced display, pixels from the current field and previous field are used in the calculations. For progressive display, pixels from the current frame and previous frame are used in the calculations.

3.2.2 Pixel level operations

The comfort noise pixel level operations use the same pre-stored Gaussian random number list and primitive polynomial generator as the film grain simulation. Three distinct primitive polynomial uniform random number patterns are used within the comfort noise generation process.

For SD resolutions, the pixel level operations are performed for all luma pixels, and the generated luma noise value is applied to both luma and chroma pixels. Let $\text{pic_width} = \text{PicWidthInSamples}_L$.

For HD resolutions, the pixel level operations are performed on $\frac{1}{4}$ of the pixels, using a 2x2 sub-sampling, and then the generated noise value applied to all pixels, using a 2x2 pel repeat. Let $\text{pic_width} = \text{PicWidthInSamples}_L \gg 1$.

P0030308

The first uniform random number pattern $x_0(i, \text{seed}_{x_0}(t))$ is initialized with a seed, $\text{seed}_{x_0}(0)=3$, at the arrival of the comfort noise SEI message. At each new frame t the uniform random number pattern is initialized to $\text{seed}_{x_0}(t)$ where $\text{seed}_{x_0}(t) = \text{seed}_{x_0}(t-1) + 2$.

The second uniform random number pattern $x_1(i, \text{seed}_{x_1}(t))$ is initialized with $\text{seed}_{x_1}(t) = \text{seed}_{x_0}(t-1)$. This implies that $x_1(i, \text{seed}_{x_1}(t)) = x_0(i, \text{seed}_{x_0}(t-1))$.

Two new numbers $\text{UN}_0(t,i)$ and $\text{UN}_1(t,i) = \text{UN}_0(t-1,i)$ are then generated from these two patterns as follows:

$$\begin{aligned}\text{UN}_0(t,i) &= x_0(i, \text{seed}_{x_0}(t)) \% 32 - 16 \\ \text{UN}_1(t,i) &= \text{UN}_0(t-1,i) = x_1(i, \text{seed}_{x_1}(t)) \% 32 - 16\end{aligned}$$

The third uniform random number generator, UN_f , is initialized to 1 at the beginning of each displayed frame and is used to generate a fixed noise image. This number generates offsets into the `Gaussian_list[]` to access a line of 8 random numbers using the following operations, where i increments for each 8 values:

$$\begin{aligned}\text{UN}_f &= x(i, 1) \\ \text{for } n=0..7, G[n] &= (\text{Gaussian_list}[(\text{UN}_f + n) \% 2048] + 1) \gg 1\end{aligned}$$

The noise value at position $[r][s]$ of the noise image is computed as

$$\begin{aligned}m &= \text{pic_width} * r + s \\ \text{noise}[r][s] &= (w_f * G[s \% 8] + w_0 * \text{UN}_0(t, m) + w_1 * \text{UN}_0(t-1, m) + 512) \gg 10\end{aligned}$$

where w_0 , w_1 , and w_f change at the block boundaries.

For SD sequences the final noise `luma_noise` is identical to noise, while for HD sequences the final noise `luma_noise` is generated by performing a 2x2 upsampling of noise using pixel repetition.

The chroma noise is half the value of the final luma noise

$$\text{chroma_noise}[r][s] = (\text{luma_noise}[r*2][s*2] + 1) \gg 1$$

Finally comfort noise shall be added to the decoded pixels and the result shall be clipped within the range of $[0, 255]$ for display.

P0030308




Figure 1. Film grain initialization process at SEI message receipt, performed for multiple blocks in each luma intensity interval




Figure 2. Film grain per block and per pixel operations

PV030308




Figure 3. Comfort noise per block operations




Figure 4. Comfort noise per pixel operations